



Particle Counters



Features and Benefits

- Particulate size range: 0.5 to 25 μm
- Up to six channels of simultaneous total and viable particle data
- Patented Laser Induced Fluorescence viability detection
- Integrated particle collection filter for off line speciation analysis
- Complies with all requirements of ISO 21501-4
- 1.0 CFM (28.3 L/min) sample flow rate
- Full optical particle counter functionality
 - Intuitive icon driven touch screen Graphical User Interface
 - Recipe based storage and recall of sampling protocols
 - Reports for ISO-14644-1, EU GMP Annex 1, and FS209E
 - 10,000 sample record storage, 999 locations
 - Ethernet and USB outputs
 - Stand-alone operation or integrate into a facility monitoring system
 - Displays up to three environmental parameters
 - Stainless steel enclosure

BioTRAK™ Real-Time Viable Particle Counter Model 9510-BD

BioTRAK Real-Time Viable Particle Counter offers best-in-class features and versatility in the exciting new field of real time airborne viable particle detection. The BioTRAK particle counter detects total and viable particle counts in real time and incorporates TSI field proven, patented Laser Induced Fluorescence (LIF) technology to determine particle viability.

Real-time viable particle detection enables:

- Immediate notification of contamination events allowing
 - Segregation of product potentially exposed to contamination
 - Initiation of root cause investigations
 - Initiation of control measures
- Trending of biological particulate levels
- Information for process improvement (PAT)
- Information for process risk management (ICH Q9)
- Feedback for gowning and aseptic process training

TSI's BioTRAK Real-Time Viable Particle Counter combines real-time viable particle detection, total particulate detection, and integrated particle collection functionality into a single portable instrument.



Specifications

Model 9510-BD

BioTRAK™ Real-Time Viable Particle Counter

Particle Counting	
Size Range	0.5 to 25 µm
Particle Channel Sizes	0.5, 0.7, 1.0, 3.0, 5.0, 10 µm
Size Resolution	<15% @ 0.5 µm (per ISO 21501-4)
Total Particulate Counting Efficiency	50% at 0.5 µm; 100% for particles >0.75 µm, (per ISO 21501-4 and JIS)
Viable Detection	2 fluorescent channels and 1 sizing channel for discrimination
Sample Collection	Integrated filter holder for 37 mm diameter filters
Concentration Limit	>400,000/ft ³ at 5% coincidence loss
Zero Count	<1 count per 5 minutes (per ISO 21501-4 and JIS B9921)
Flow Rate	1.0 CFM (28.3 L/min) ±5% accuracy (meets ISO 21501-4 and JIS B9921)
Calibration	NIST traceable using TSI calibration system
Calibration Frequency	Recommended minimum of once per year
Standards	ISO 21501-4, CE, JIS B9921
Hardware	
Total Particulate Light Source	685 nm laser diode for MIE particle sizing
Viable Particulate Light Source	405 nm laser diode for Laser Induced Fluorescence viability detection
Flow Rate Control	Electronic, automatic closed loop (patented* flow control technology)
Sample Tube Extension	Up to 10 ft (3 m)
Audible Alarm	Built-in; >85 dB at 1 meter (adjustable)
Exhaust	Internal HEPA filter
Vacuum Source	Internal pump
Alarm Output	Dry contacts, closed when alarm is engaged
Display	VGA 5.7-in. (14.5-cm) touch screen display
Printer	Optional built-in thermal printer
Dimension (H x W x D)	19 in. x 10.5 in. x 13.5 in. (48.3 cm x 26.7 cm x 34.3 cm)
Weight	41 lbs (18.6 kg)
Power	110 to 240 VAC universal power supply
Operating Range	41° to 95°F (5° to 35°C), 20% to 95% RH noncondensing
Storage Range	32° to 122°F (0° to 50°C), up to 98% RH noncondensing

Hardware (continued)	
Housing	Stainless Steel
External Chemical Resistance	Isopropyl alcohol, chlorinated solution, hydrogen peroxide
Environmental Sensor Interface	Supports TSI air velocity, temperature and relative humidity probes
User Interface and Communication	
Sampling Modes	Manual, automatic, beep; cumulative/differential; count or concentration
Sampling Time	1 second to 99 hours
Sampling Frequency	1 to 9999 cycles or continuous
Data Storage	10,000 sample records: includes date, time, six particle channels, flow, ID, and sample volume; transferable via USB storage device and TRAKPro™ Lite Secure software
Status Indicators	Flow, laser
Alarm Limits	Programmable for all particle channels (both total and viable)
Languages	English, German, French, Spanish, Japanese, Chinese (simplified), Italian
Software	TRAKPro™ Lite Secure, optional FMS software
Printer Output	Prints in all available languages
Unit ID	Configurable IP address
Security	2-level password protection to lock out usage and configuration
Location ID	Up to 999 Locations; 16 characters long
Reports	Provides Pass/Fail on ISO 14644-1, EU GMP, and FS209E reports
Communication Mode	Modbus® TCP over Ethernet or USB
Accessories	
Included Accessories	Printed QuickStart guide, operating manual on CD, power supply, isokinetic probe, tripod, tubing, purge filter, USB cable, TRAKPro™ Lite Secure software, viable filter holder, calibration certificate
Optional Accessories	Electronic filter scanning probe, basic filter scanning probe, TSI velocity probes, Temp/RH probe, isokinetic probes, sample tubing, hard-sided carrying case, printer paper, viable filter holder, viable collection filters, FMS Software

*The BioTrak 9510-BD incorporates the following patented technologies: Patent Numbers 6,167,107; 5,701,012; 5,895,922; 6,831,279; 7,261,007.

Specifications are subject to change without notice. TSI, the TSI logo, BioTRAK, and TRAKPro are trademarks of TSI Incorporated.

Modbus is a registered trademark of Modicon, Inc.

TSI Incorporated - 500 Cardigan Road, Shoreview, MN 55126-3996 USA

USA	Tel: +1 800 874 2811	E-mail: answers@tsi.com	Website: www.tsi.com
UK	Tel: +44 149 4 459200	E-mail: tsiuk@tsi.com	Website: www.tsiinc.co.uk
France	Tel: +33 491 11 87 64	E-mail: tsifrance@tsi.com	Website: www.tsiinc.fr
Germany	Tel: +49 241 523030	E-mail: tsigmbh@tsi.com	Website: www.tsiinc.de
India	Tel: +91 80 41132470	E-mail: tsi-india@tsi.com	
China	Tel: +86 10 8251 6588	E-mail: tsibeijing@tsi.com	
Singapore	Tel: +65 6595 6388	E-mail: tsi-singapore@tsi.com	



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website www.tsi.com for more detailed specifications.